

YONKANG HALL LIGHTING EQUIPMENT

Local Power Supply					
230 volt single phase, 60Hz					
Standard stage fixture connector		ProPin Professional Stage Pin Connectors			
Standard household connector		20A PP2PGCM & Pro Series PS19 (19 Pin Connectors)			
Control System					
Console		Grand MA3 Light	2	MA Lighting	
Processing		Processing Unit L	1		
Backup System: Grand MA3 Light With Switcher(Backup 4 Switch RS 8000N)					
Dimming System					
Dimmer		Sensor+	3 Sets	ETC	5kW / 278 Dimmer (Dual Type)
					5kW / 10 ThruPower (Dual Type)
Direct Module		Sensor+	20	ETC	5kW / (Dual Type)
Fixture					
E.R.S	15° ~ 30°	Source-Four Zoom / 750W	36	ETC	
	25° ~ 50°		36		
	19°	Source-Four Standard / 750W	12		EDLT
	26°		48		
	36°		48		
	50°		12		
Lens Tube	5°	For Source-Four Standard	2		
	10°		2		
Fresnel		FQH - 1kW S1	30	Marumo	With Barn door
		FQH - 2kW S1	6		
PAR64		1kW	60		
PAR46		250W	20 Sets		1 Set = 8EA / ACL
Zip Strip		ZS-3 / 1.5kW Per Circuit	4 Sets	Altman	1 Set = 2EA = 3 Circuit / ACL
Follow Spot Light		Xevex - 2kW	2	Ushio	Fixed
Effect					
Strobe		Atomic 3000 DMX	2	Martin	
Accessory					
Iris			25	Kupo	For Source-Four
Top Hat	Half	4 Inch	12		For Source-Four Standard
	Wide	4 Inch	12		
	Standard	4 Inch	72		
		6 Inch	60		For Source-Four Zoom
		8 Inch	18		For PAR64
T - Pipe		60cm(W)	30		
Stand	Long	2.5m	10		
	Middle	1m	10		
	Short	SHB-5 / 6cm	10	Marumo	
Side Arm		90cm	16	Altman	
		60cm	10		
Ladder		145cm(H) x 120cm(W)	4		
		80cm(H) x 120cm(W)	4		